

# TIGER Neo

## 66HL4M-BDV

### 605-630 Watt

BIFACIAL MODULE WITH DUAL GLASS

### N-type



### N-Type Technology

N-Type modules with Tunnel Oxide Passivating Contacts (TOPcon) technology offer lower LID/LeTID degradation and better low light performance.



### HOT 3.0 Technology

N-type modules with JinkoSolar's HOT 3.0 technology offer better reliability and efficiency.



### Dual-Sided Power Generation

Dual-sided power generation gain increases with backside exposure to light, significantly reducing LCOE.



### Mechanical Load Enhanced

Certified to withstand:  
5400 Pa front side max static test load  
2400 Pa rear side max static test load




### SMBB Technology

Better light trapping and current collection to improve module power output and reliability.



### Anti-PID guarantee

Minimizes the chance of degradation caused by PID phenomena through optimization of cell production technology and material control.



**12 Year**  
Product Warranty

**30 Year**  
Linear Power Warranty

**1%**  
First-year Degradation

**0.4%**  
Annual Degradation Over 30 Years

- IEC61215:2021 / IEC61730:2023
- IEC61701 / IEC62716 / IEC60068 / IEC62804
- ISO9001:2015: Quality Management System
- ISO14001:2015: Environment Management System
- ISO45001:2018: Occupational health and safety management systems



EU-JKM605-630N-66HL4M-BDV-F3-EN

# 66HL4M-BDV 605-630 Watt

## Mechanical Characteristics

Cell Type	N type Mono-crystalline
No. of cells	132 (66×2)
Dimensions	2382×1134×30 mm
Weight	32.2 kg
Front Glass	2.0 mm, Anti-Reflection Coating
Back Glass	2.0 mm, Heat Strengthened Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP68 Rated
Protection Class	Class II
IEC Fire Type	Class C
Output Cables	4.0mm <sup>2</sup> (+): 400mm , (-): 200mm or Customized Length

## Packaging Configuration

Pallet Dimensions	2396×1110×1251 mm
Packing detail (Two pallets=One stack)	36 pcs/pallets, 72 pcs/stack, 720 pcs/40'HQ Container

## Specifications (STC)

Maximum Power – Pmax [Wp]	605	610	615	620	625	630
Maximum Power Voltage – Vmp [V]	40.31	40.46	40.60	40.74	40.88	41.02
Maximum Power Current – Imp [A]	15.01	15.08	15.15	15.22	15.29	15.36
Open-circuit Voltage – Voc [V]	48.48	48.68	48.88	49.08	49.28	49.48
Short-circuit Current – Isc [A]	15.90	15.96	16.02	16.08	16.14	16.20
Module Efficiency STC [%]	22.40	22.58	22.77	22.95	23.14	23.32
Power Tolerance	0 ~ +3 %					
Temperature Coefficients of Pmax	-0.29 %/°C					
Temperature Coefficients of Voc	-0.25 %/°C					
Temperature Coefficients of Isc	0.045 %/°C					

STC: Irradiance 1000W/m<sup>2</sup>, Cell Temperature 25°C, AM=1.5

## Specifications (BNPI)


Maximum Power – Pmax [Wp]	668	674	679	685	690	696
Maximum Power Voltage – Vmp [V]	40.29	40.46	40.59	40.75	40.88	41.04
Maximum Power Current – Imp [A]	16.58	16.66	16.73	16.81	16.88	16.95
Open-circuit Voltage – Voc [V]	48.46	48.66	48.86	49.06	49.26	49.46
Short-circuit Current – Isc [A]	17.56	17.64	17.70	17.77	17.83	17.90

BNPI: Irradiance front 1000W/m<sup>2</sup>, rear 135 W/m<sup>2</sup>, Cell Temperature 25°C, AM=1.5

## Application Conditions



Operating Temperature	-40 °C ~ +70 °C
Maximum System Voltage	1500 VDC (IEC)
Maximum Series Fuse Rating	35 A
Bifaciality Coefficient	φVoc: 98±5 %, φIsc: 80±5 %, φPmax: 80±5 %

## Engineering Drawings



**Note:** For specific dimensions and tolerance ranges, please refer to the corresponding detailed module drawings.

## Electrical Performance



© 2024 Jinko Solar Co., Ltd. All rights reserved.

**Note:** Please read the safety and installation manual before using the product. We reserve the right of final interpretation. The specifications in this datasheet are subject to change without notice.

EU-JKM605-630N-66HL4M-BDV-F3-EN

www.jinkosolar.com  
www.jinkosolar.eu